

PJ**PL****PM**

PJ			PL			PM		
Belt ref.		Effective length	Belt ref.		Effective length	Belt ref.		Effective length
DIN 7867	RMA	mm DIN/ISO	DIN 7867	RMA	mm DIN/ISO	DIN 7867	RMA	mm DIN/ISO
PJ 457	180 J	457	PL 1270	500 L	1270	PM 2286	900 M	2286
PJ 483	190 J	483	PL 1371	540 L	1371	PM 2388	940 M	2388
PJ 508	200 J	508	PL 1422	560 L	1422	PM 2515	990 M	2515
PJ 559	220 J	559	PL 1562	615 L	1562	PM 2693	1060 M	2693
PJ 584	230 J	584	PL 1613	635 L	1613	PM 2832	1115 M	2832
PJ 610	240 J	610	PL 1664	655 L	1664	PM 2921	1150 M	2921
PJ 660	260 J	660	PL 1715	675 L	1715	PM 3010	1185 M	3010
PJ 711	280 J	711	PL 1764	695 L	1764	PM 3124	1230 M	3124
PJ 762	300 J	762	PL 1841	725 L	1841	PM 3327	1310 M	3327
PJ 813	320 J	813	PL 1943	765 L	1943	PM 3531	1390 M	3531
PJ 838	330 J	838	PL 1981	780 L	1981	PM 3734	1470 M	3734
PJ 864	340 J	864	PL 2020	795 L	2020	PM 4089	1610 M	4089
PJ 914	360 J	914	PL 2070	815 L	2070	PM 4191	1650 M	4191
PJ 965	380 J	965	PL 2134	840 L	2134	PM 4470	1760 M	4470
PJ 1016	400 J	1016	PL 2197	865 L	2197	PM 4648	1830 M	4648
PJ 1041	410 J	1041	PL 2324	915 L	2324	PM 5029	1980 M	5029
PJ 1067	420 J	1067	PL 2476	975 L	2476	PM 5410	2130 M	5410
PJ 1092	430 J	1092	PL 2515	990 L	2515	PM 6121	2410 M	6121
PJ 1118	440 J	1118	PL 2705	1065 L	2705	PM 6502	2560 M	6502
PJ 1168	460 J	1168	PL 2845	1120 L	2845	PM 6883	2710 M	6883
PJ 1219	480 J	1219	PL 2921	1150 L	2921	PM 7646	3010 M	7646
PJ 1244	490 J	1244	PL 3086	1215 L	3086	PM 8408	3310 M	8408
PJ 1270	500 J	1270	PL 3125	1230 L	3125	PM 9169	3610 M	9169
PJ 1321	520 J	1321	PL 3289	1295 L	3289			
PJ 1397	550 J	1397	PL 3327	1310 L	3327			
PJ 1473	580 J	1473	PL 3696	1455 L	3696			
PJ 1549	610 J	1549						
PJ 1651	650 J	1651						
PJ 1854	730 J	1854						
PJ 2210	870 J	2210						
PJ 2337	920 J	2337						
PJ 2489	980 J	2489						

All dimensions are available from stock in following rib widths:

Number of ribs PJ section	Number of ribs PL & PM sections
4	6
6	8
10	10
16	12
20	14
	16
	18
	20

Other rib widths are available on request.

Standard Belt Nomenclature

The Micro-V® belt is correctly identified by a three part symbol consisting of:

1. number of ribs;
2. cross-section;
3. effective length designation in mm.

Example:

belt designation 10 PL 2020 stands for:

1. 10 ribs in width;
2. section L (PL indicates a metric belt);
3. effective length of 2020 mm.